
MICRO CALIBRATION BATH

portable, 35 °C to 200 °C



Dimensions (in mm):



264 x 203 x 140 mm

Options:

CAL-9930 : software package (windows®) included in price


CAL-9932 : extended software package

General:

The model CAL-6102 is truly portable bath, which makes it the perfect calibration instrument for just any sized temperature sensor. Its 130 mm deep stirred temperature well is stable to within \pm 0,03 °C over its range of ambient to 200 °C. It works great for large diameter, short stem, liquid-in-glass, or odd shaped probes that are difficult to calibrate in a dry-well. The diameter of the tank is 63,5 mm, so you can immerse almost any size sensor. There is no need to drain the tank fluid before you carry this microbath to another location. Simply screw the o-ring sealed lid onto the tank and transport it spill-free.

Accessories:

CAL-3224	:	spare transport/pour cover
CAL-3225	:	spare test lid
CAL-3226	:	spare probe basket
CAL-3227	:	spare stir bar
CAL-3228	•	spare pour spout
CAL-3229	•	spare pour spout cover
CAL-3230	:	spare transport plug
CAL-3231	:	76,2 mm extension adapter
CAL-3232	:	o-ring cover



Tel.: +31 (0)182 – 302 850 Fax: +31 (0)182 – 302 777 E-mail: info@thermo-electric.nl Internet: http://www.thermo-electric.nl

J/620r