SPRINGLOADED THERMOCOUPLES

with silver tip

Ordering code:

FIXED IMMERSION TYPES:

single	Silver tip 'A' 'B' MTS-60121 - □ - □ mm	Mi-cable construction 'A' 'B' MTS-65121 mm	LEAD LENGTH "B"
duplex		MTS-65221 - □ - □ mm	Straight, probe with lead wire and bare ends
single duplex	'A' 'B' MTS-61121 -⊡-⊡mm	'A' 'B' MTS-66121 -□-□mm MTS-66221 -□-□mm	LEAD LENGTH "B"
			Angled, probe with lead wire and bare ends
single duplex	'A' 'B' MTS-60131 -⊡-⊡mm	'A' 'B' MTS-65131 -□-□mm MTS-65231 -□-□mm	LEAD LENGTH "9"
			Straight, probe with lead wire and standard plug
single duplex	'A' 'B' MTS-61131 -□-□mm	'A' 'B' MTS-66131 -□-□mm MTS-66231 -□-□mm	LEAD LENGTH "B"
			Angled, probe with lead wire and standard plug
single	'A' MTS-60101 -⊡mm		
			Straight, probe with directly mounted standard plug
single	'A' MTS-61101 -⊡mm		Angled, probe with directly mounted standard plug
			Angrea, probe with unectry mounted standard plug

ADJUSTABLE IMMERSION TYPES:



Straight, probe with lead wire and standard plug

Information on immersion lengths, mounting and pipe clamp adapters for use with springloaded thermocouple, see datasheet B/510.

Options / Accessories:

Duplex Mi-cable thermocouples with duplex plug for direct connection to 2-circuit panel, and junction box connector with 1/2 inch NPT on lead wire types with bare ends only.

Mating jack : ordering code CNN-12100-J-BK

Mounting adapters : see datasheet B/510



Tel.: +31 (0)182 - 302 850 Fax: +31 (0)182 - 302 777 E-mail: info@thermo-electric.nl Internet: http://www.thermo-electric.nl

B/500r