


THERMOCOUPLE WIRE

fibreglass insulated, twisted; 650 °C



Features:

- Max. temperature up to 800 °C
- High thermal endurance
- Easy to install
- Additional armoring available

Applications:

- Heat treatment
- Steel and aluminium industry
- Ovens

Specifications:

Conductors	:	solid, thermocouple grade materials
Insulation	:	high-strength fibreglass impregnated
Construction	:	twisted conductors
Operating temperature (max.)	:	650 °C
Limits of error	:	according to ANSI MC 96.1/IEC-584
Colour code	:	according to ANSI MC 96.1/IEC-584 others optional

Dimensions and weight:

(nominal values)

Conductor size

AWG	∅ mm	outer ∅ mm	weight/km
20	0,8	1,8 x 3,8	16,4 kg
22	0,65	1,4 x 2,9	11,5 kg

Ordering code:

Calibration

Iron-constantan
Chromel-Alumel

20 AWG

Q/Tw-20-JJ ANSI 9151687
Q/Tw-20-KK ANSI
Q/Tw-20-KK IEC 9151707

Stock number

22 AWG

Q/Tw-22-KK ANSI
Q/Tw-22-KK IEC 9151705

Stock number



Thermo Electric
P.O. Box 179
2740 AD Waddinxveen
The Netherlands

Tel. : +31 (0)182 – 302 850
Fax : +31 (0)182 – 302 777
E-mail : info@thermo-electric.nl
Internet: http://www.thermo-electric.nl

E/1.450
Rev.00 08/03