

THERMOCOUPLE EXTENSION CABLES

dimensions & weights

Specifications:

Thermo cable type : P/ALPTWK-....-20-JX/KX/TX
overall shielded, PVC insulated thermocouple extension cable
Datasheet number : 3.150

Dimensions and weights:

(values stated are nominal dimensions in millimetres)

no. of pairs	outer jacket thickness	outer diameter	min. bend radius	tension loading (kg)	nett weight kg/km
1	0.9	5.5	38	11	39
2	1.1	8.2	50	19	76
4	1.1	9.3	57	34	110
6	1.3	11.2	70	49	159
8	1.3	12.2	76	63	193
10	1.3	13.6	83	78	232
12	1.3	14.2	83	93	263
16	1.6	16.3	95	122	349
20	1.6	17.0	102	152	412
24	1.6	19.1	114	182	485
36	1.9	22.1	127	271	673
50	1.9	25.2	146	374	923

Specifications:

Thermo cable type : P/ALM/ALPTWK-....-20-JX/KX/TX
individual and overall shielded, PVC insulated thermocouple extension cable
Datasheet number : 3.151

Dimensions and weights:

(values stated are nominal dimensions in millimetres)

no. of pairs	outer jacket thickness	outer diameter	min. bend radius	tension loading (kg)	nett weight kg/km
2	1.1	9.4	76	24	92
4	1.3	11.4	89	44	152
6	1.3	13.4	108	64	204
8	1.3	14.5	114	83	250
10	1.6	17.4	140	103	324
12	1.6	17.4	140	119	364
16	1.6	19.3	152	159	455
20	1.6	21.4	172	198	548
24	1.9	23.7	191	238	666
36	1.9	26.3	210	357	920
50	1.9	30.7	241	497	1231



Thermo Electric
P.O. Box 179
2740 AD Waddinxveen
The Netherlands

Tel. : +31 (0)182 – 302 850
Fax : +31 (0)182 – 302 777
E-mail : info@thermo-electric.nl
Internet: http://www.thermo-electric.nl

F/003
Rev.00 08/03