

HANDHELD THERMOMETER

for use with hand held indicators


Specifications:

Type	: single thermocouples
Calibration	: Chromel-alumel (type K)
Connector	: Thermo Electric miniature plug
Max. recommended temperature	: see tip detail
Dimensions	: in mm


Ordering code:

SURFACE PROBE:

HHP-50151: 4,8 mm o.d.



tip detail:




500 °C*


GENERAL PURPOSE PROBE:

HHP-60151: 1,5 mm o.d.

HHP-60251: 3,0 mm o.d.




tip detail:



850 °C*

SPRINGLOADED SURFACE PROBE:

HHP-50351: 8 mm o.d.




tip detail:




BENT SURFACE PROBE:

HHP-50251: 8 mm o.d.



tip detail:




200 °C*


NEEDLE PROBE:

HHP-40081: 1,5 mm o.d.

HHP-40181: 3,0 mm o.d.



tip detail:



500 °C*

* Temperatures mentioned are the maximum recommended temperatures



Thermo Electric
P.O. Box 179
2740 AD Waddinxveen
The Netherlands

Tel. : +31 (0)182 – 302 850
Fax : +31 (0)182 – 302 777
E-mail : info@thermo-electric.nl
Internet : <http://www.thermo-electric.nl>

K/145